





Photoluminescent self-adhesive film

Model	Thick (mm)	Size	AFTERGLOW INTENSITY(mcd/m ²)		Appearance (Daytime)	Glowing color	Material
			10 min	60min			
PLE-V-Z-G050P	0.30	1M*10	>50	>5	 Light-yellow	 Yellow-green	PVC
PLE-V-Z-G100	0.35	M	>100	>10			
		1M*25					
PLE-V-Z-G150	0.35	M	>150	>20			
		1M*50					
PLE-V-Z-G200	0.35	M	>210	>30			
PLE-V-Z-G300	0.40		>300	>35			
PLE-V-Z-G500	0.65		>500	>68			
PLE-V-M-B200	0.35		>170	>18	Light-white	Bule-green	
PLE-V-M-SB200	0.35		>100	>15	Light-white	Blue	
PLE-V-C-R200	0.35		>60	>9	red	Orange-Red	
PLE-V-Ze-G200	0.35		>80	>10	Green	Green	
PLE-V-Z-Y200	0.35		>110	>15	Yellow	Yellow	
PLE-V-O-O200	0.35		>60	>9	Orange	Orange	
PLE-V-M-BB200	0.35		>40	>5	Blue	Blue	
PLE-VP-Z-G200	0.5	0.91*10m	>210	>30	Light-yellow	Yellow-gree	Non-slip surface
PLE-V-Z-GP050	0.30	1.23M*10m	>50	>5	 Light-yellow	 Yellow-green	PET
PLE-V-Z-GP100	0.35	or 25m	>100	>10			
PLE-V-Z-GP150	0.35	or 50m	>150	>20			
PLE-V-Z-GP200	0.35		>210	>30			

1.The aferglow brightness is measured under D65 standard light source after being excited for 5 min by 1000 LUX.

2. Special size or width and so on of photoluminescent film;we can be processed based on customers' requirement, but the price will have change.
3. This film can be printed by laser printer or inkjet printer(solvent ink)
4. if the vinyl without self-adhesive.