









Photoluminescent self-adhesive film

Series	Model	Thick (mm)	Size	AFTERGLOW INTENSITY(mcd/m ²)		Appearance (Daytime)	Glowing color
				10 min	60min		
PVC-P Series	PLE-V-Z-G030P	0.30	1M*25M	>23	>3	 Light-yellow	 Yellow-green
	PLE-V-Z -G050P	0.30	1M*50M	>50	>7		
	PLE-V-Z -G100P	0.35		>100	>12		
	PLE-V-Z -G150P	0.35		>150	>20		
	PLE-V-Z -G200P	0.35		>210	>30		
	PLE-V-Z -G300P	0.40		>300	>35		
	PLE-V-Z -G500P	0.65		>500	>68		
	PLE-V-MZ-B200P	0.35	>170	>18	Light-white	Bule-green	
	PLE-V-M-SB200P	0.35	>100	>15	Light-white	Blue	
	PLE-V-C-R200P	0.35	>60	>9	red	Orange-Red	
	PLE-V-Ze-G200P	0.35	>80	>10	Green	Green	
	PLE-V-Z-Y200P	0.35	>110	>15	Yellow	Yellow	
	PLE-V-O-O200P	0.35	>60	>9	Orange	Orange	
	PLE-V-M-B200P	0.35	>40	>5	Blue	Blue	
PVC Series	PLE-V-Z -G100	0.35	1*50m	>100	>10	 Light-yellow	 Yellow-green
	PLE-V-Z -G150	0.35	1.23*50m	>150	>20		
	PLE-V-Z -G200	0.35		>210	>30		
	PLE-V-Z -G300	0.40		>300	>35		
Acrylic Series	PLE-V-Z -GA100	0.16	1.23*50M	>100	>12	 Light-yellow	 Yellow-green
	PLE-V-Z -GA150	0.21		>150	>20		
	PLE-V-Z -GA200	0.25		>210	>30		
	PLE-V-Z -GA300	0.40		>300	>35		
PET Series	PLE-V-Z -GP030	0.30	1.23*50m	>23	>3	 Light-yellow	 Yellow-green
	PLE-V-Z -GP050	0.30		>50	>5		
	PLE-V-Z -GP100	0.35		>100	>10		
	PLE-V-Z -GP150	0.35		>150	>20		
	PLE-V-Z -GP200	0.35		>210	>30		
Non-slip Series	PLE-SFP-G200	0.5	1.2*50M	>210	>30	Light-yellow	Yellow-gree
	PLE-SFP-G400	0.65		>400	>50		
Thermal Transfer Series	PLE-TF-G150	0.17	0.61*10M	>150	>20	Light-yellow	Yellow-gree
	PLE-TF-B150	0.17		>120	>17	Light-white	Bule-green

1. The afterglow brightness is measured under D65 standard light source after being excited for 5 min by 1000 LUX.

2. **PVC-P Series:** PVC material, no warping, no delamination, Non flammability, easy for inkjet and silk-screen.



www.photoluminescenteurope.com

www.photoluminescenteshop.com

Manželů Dostálových 1213

198 00 Prague 14

www.pleu.cz

IČO: 0344350

DIČ: CZ03443507

Bank account : 2400678004/2010

IBAN: CZ8720100000002400678004

BIC/SWIFT: FIOBCZPPXXX

info@pleu.cz

-
3. **PVC Series:**PVC material , no delamination, Non-flammable, could be for inkjet printing, easy for silk-screen.
 4. **Acrylic Series:** Acrylic material, weather resistance excellence, easy for silk-screen, flammable, matt.
 5. **PET Series:** PET material ,suitable for engraving, not easy for printing.
 6. **Thermal Transfer Series:**PU material ,suitable for engraving, then applied to fabric or liner through heat transfer by iron.
 7. Special size or width and so on of photoluminescent film;we can be processed based on customers' requirement, but the price will have change.